

NE10003-208423

10*1GE Copper EN50155 L2 Managed PoE++ Industrial Switch



Product Features

- ✧ 10*10/100/1000Base-T M12 copper ports
- ✧ 8 downlink Gigabit copper ports support PoE/PoE++/PoE++, compatible with IEEE 802.3af/at/bt standards
- ✧ Each PoE/PoE+/PoE++ port can supply up to 15W/30W/60W
- ✧ Supports ERPS/RSTP & X-Ring Self-healing Ring
- ✧ Supports IEEE 802.1X, supports secure access management, enhancing network security

Product Overview

The NE10003-208423 is a 10-port full Gigabit L2 managed Industrial Ethernet Switch specially designed for rail transportation. This product meets the EN50155 industry standard requirements and complies with the IEEE 802.3af/at/bt protocol standards. The Ethernet interface adopts a sturdy and reliable M12 format, making it suitable for scenarios with severe vibrations and impacts. The product offers 10 * 1GE M12 ports. This series of switches has a working temperature range of -40°C to +80°C and features an IP68-rated shell and LED indicators, making it a plug-and-play industrial-grade device. With its exceptional waterproofing and ruggedness, it can adapt to various harsh environments, providing users with a reliable and convenient solution for networking their Ethernet devices.

Product Specifications

Series	NE10003-208423	
Ports	10 * 10/100/1000 Base-T(X) M12 copper X coded female Ethernet ports	
	Automatic detection, full/half duplex MDI/MDI-X self adaptive	
	1 * M12 Input power port(dual power redundancy)	
Ethernet Standards	IEEE 802.3: 10Base-T Ethernet; IEEE 802.3u: 100Base-TX Fast Ethernet; IEEE 802.3ab: 1000Base-T Gigabit Ethernet IEEE 802.3x: Follow Control	
Certification	EN50155	
MTBF	300,000 hours	
Warranty	3 years	
Industry Standards	EMI	FCC Part 15 Subpart B Class A,EN 55022 Class A
	EMS	IEC(EN)61000-4-2(ESD): ± 8kV touch discharge, ± 15kV air discharge
		IEC(EN)61000-4-3(RS): 10V/m(80~1000MHz)
		IEC(EN)61000-4-4(EFT) : power cable: ±4kV Data cable: ±2kV;

		IEC(EN)61000-4-5(Surge) : power cable: $\pm 2\text{kV}$ CM// $\pm 4\text{kV}$ DM ; Data cable: $\pm 4\text{kV}$
		IEC(EN)61000-4-6(Radio frequency conduction) : 3V(10kHz~150kHz),10V(150kHz~80MHz)
		IEC(EN)61000-4-16(Common-mode conduction) : 30V cont. 300V,1s
		IEC(EN)61000-4-8
	Shock	IEC 60068-2-27
	Free Fall	IEC 60068-2-32
	Vibration	IEC 60068-2-6

Switching Parameters

Transmission Method	Store and forward
Backplane Bandwidth	20G
MAC capacity	16K
Switching Latency	$<10\mu\text{s}$
Cache	2 Mbit
Power Consumption	$<5\text{W}$

Working Temperature

Working Temperature	$-40\sim 80^{\circ}\text{C}$ ($-40\sim 176^{\circ}\text{F}$)
Storage Temperature	$-40\sim 85^{\circ}\text{C}$ ($-40\sim 185^{\circ}\text{F}$)
Relative Humidity	5%~95% without condensation

PoE Features

PoE Standards	IEEE802.3af/ IEEE802.3at/ IEEE802.3bt
PoE Ports	8 ports supports PoE++, automatically detects the standards of devices like IEEE802.3af , IEEE802.3at and IEEE802.3bt
Output Power	IEEE 802.3af: max. 15.4W/port
	IEEE 802.3at: max. 30W/port,
	IEEE 802.3bt: max. 90W/port,
	Total maxW:200W
POE Priority	When power $>200\text{w}$, POE priority: port No.8>port No.7>port No.6 and so on

Power Parameters

Input Voltage	DC48V
Access Terminal	M12 A male port
Power Protection	Supports dual power supply redundancy Supports reverse polarity protection

Mechanical Features

Shell	IP67, aluminum enclosure
-------	--------------------------

Installation Method	Wall mounted
Cooling Method	Natural cooling, fanless
Weight	1.13kg
Size	186 x 121 x 30mm
LED Indication	
Power Indicator	PWR
Interface Indicator	Copper ports(Link/ACT)

Mechanical Diagram

Size: 186 x 121 x 30mm

