

Technical data Part-turn actuators for open-close duty

General information

SQV part-turn actuators with variable speed. AUMA actuator controls of the ACV type are required to change the operating time.

Type	Operating time for 90°	Torque range ¹⁾		Run torque ²⁾	Number of starts
	[s]	Min. [Nm]	Max. ³⁾ [Nm]	Max. [Nm]	Starts Max. [1/h]
SQV 05.2	4 – 28	50	150	52	60
	12 – 120				
SQV 07.2	4 – 28	100	300	105	60
	12 – 120				
SQV 10.2	12 – 120	200	600	210	60
SQV 12.2	24 – 240	400	1,200	420	60
SQV 14.2	40 – 360	800	2,400	840	60

- 1) The tripping torque is adjustable for directions OPEN and CLOSE within the indicated torque range.
- 2) Permissible average torque for a travel of 90°.
- 3) Maximum torque to approx. 50 % of shortest operating time.

Valve attachments and weight

Type	Valve attachment		Valve shaft			Handwheel		Weight
	Standard EN ISO 5211	Option EN ISO 5211	Cylindrical Max. [mm]	Square Max. [mm]	Two-flat Max. [mm]	Ø [mm]	Turns for 90°	approx. [kg]
SQV 05.2	F05/F07	F10	25.4	22	22	160	11	21 ¹⁾
							16	27 ²⁾
SQV 07.2	F05/F07	F10	25.4	22	22	160	11	21 ¹⁾
							16	27 ²⁾
SQV 10.2	F10	F12	38	30	27	200	11	26 ¹⁾
							16	31 ²⁾
SQV 12.2	F12	F14	50	36	41	200	11	35 ¹⁾
							16	43 ²⁾
SQV 14.2	F14	F16	60	46	46	200	11	44 ¹⁾
								55 ²⁾

- 1) Indicated weight includes part-turn actuator with electrical connection in standard version, unbored coupling and handwheel.
- 2) Indicated weight includes part-turn actuator with electrical connection in standard version, unbored coupling and handwheel, including base and lever.

Features and functions

Type of duty	Short-time duty S2 - 15 min, classes A and B according to EN SO 22153 For nominal voltage, +40 °C ambient temperature and at load with 35 % of the max. torque.	
Motors	3-phase AC asynchronous squirrel-cage motor, type IM B9 according to IEC 60034-7, IC410 cooling procedure according to IEC 60034-6	
Mains voltage, mains frequency	Voltages: Refer to table: 3-phase AC standard voltages [► 2] Refer to table: 1-phase AC standard voltages [► 2] Permissible variation of mains voltage: ±10 % Permissible variation of mains frequency: -5 %	
Overvoltage category	Category III according to IEC 60364-4-44	
Insulation class	Standard:	F, tropicalized
	Option:	H, tropicalized
Motor protection	Standard:	Thermoswitches (NC)
	Option:	PTC thermistors (according to DIN 44082)
Motor heater (option)	Voltages: 110 – 120 V AC, 220 – 240 V AC or 380 – 480 V AC	
	Power 12.5 W	
Self-locking	Yes (actuators are self-locking if the valve position cannot be changed from standstill while torque acts upon the output drive.)	
Swing angle	Standard:	Adjustable between 75° and < 105°
	Options:	15° to < 45°, 45° to < 75°, 105° to < 135°, 135° to < 165°, 165° to < 195°, 195° to < 225°
Manual operation	Manual drive for setting and emergency operation, handwheel does not rotate during electrical operation.	
	Options:	Handwheel lockable Handwheel stem extension Power tool for emergency operation with square 30 mm or 50 mm

Technical data Part-turn actuators for open-close duty

Features and functions		
Indication for manual operation (option)	Indication whether manual operation is active/not active via single switch (1 change-over contact)	
Electrical connection	Standard:	AUMA plug/socket connector with screw-type connection
	Options:	Terminals or crimp-type connection Gold-plated control plug (sockets and pins)
Threads for cable entries	Standard:	Metric threads
	Option:	Pg threads, NPT threads, G threads
Terminal plan	TPA00R100-011-000 (basic version)	
Splined coupling for connection to the valve shaft	Standard:	Coupling without bore
	Options:	Machined coupling with bore and keyway, square bore or bore with two-flats according to EN ISO 5211
Valve attachment	Dimensions according to ISO 5211 without spigot	

Table 1: 3-phase AC standard voltages

Voltages/frequencies				
Volt [3~]	220 – 240	220 – 240	380 – 480	380 – 480
Hz	50	60	50	60

Table 2: 1-phase AC standard voltages

Voltages/frequencies				
Volt [1~]	110 – 120	110 – 120	220 – 240	220 – 240
Hz	50	60	50	60

With base and lever (option)	
Swing lever	Made of spheroidal cast iron with two or three bores for fixing a lever arrangement. Considering the installation conditions, the lever may be mounted to the output shaft in any desired position.
Ball joints (option)	Two ball joints matching the lever, including lock nuts and two welding nuts, suitable for pipe according to dimension sheet.
Fixing	Base and four holes for fastening screws

Electronic control unit	
Non-intrusive settings	Magnetic limit and torque transmitter (MWG)
Position feedback signal	Via actuator controls
Torque feedback signal	Via actuator controls
Running indication	Blinking signal via actuator controls
Heater in switch compartment	Resistance type heater with 5 W, 24 V AC

Service conditions	
Use	Indoor and outdoor use permissible
Mounting position	Any position
Installation altitude	≤ 2,000 m above sea level > 2,000 m above sea level on request
Ambient temperature	Standard: –30 °C to +70 °C
	Options: –40 °C to +70 °C –60 °C to +60 °C
Humidity	Up to 100 % relative humidity across the entire permissible temperature range
Enclosure protection in accordance with IEC 60529	Standard: IP68 with AUMA 3-phase AC motor For special motors, differing enclosure protection is possible
	Option: Terminal compartment additionally sealed against interior of actuator (double sealed)
	According to AUMA definition, enclosure protection IP68 meets the following requirements: • Depth of water: maximum 8 m head of water • Continuous immersion in water: maximum 96 hours • Up to 10 operations during immersion
Pollution degree according to IEC 60664-1	Pollution degree 4 (when closed), pollution degree 2 (internal)
Vibration resistance according to IEC 60068-2-6	2 g, 10 to 200 Hz (AUMA NORM) 1 g, 10 to 200 Hz (for actuators with ACV actuator controls) Resistant to vibration during start-up or for plant failures. However, a fatigue strength may not be derived from this. Not valid in combination with gearboxes.

Technical data Part-turn actuators for open-close duty

Service conditions		
Corrosion protection	Standard:	KS: Suitable for use in areas with high salinity, almost permanent condensation, and high pollution.
	Option:	KX: Suitable for use in areas with extremely high salinity, permanent condensation, and high pollution.
Coating	Double layer powder coating	
Colour	Standard:	AUMA silver-grey (similar to RAL 7037)
	Option:	Available colours on request
Lifetime	AUMA part-turn actuators meet or exceed the lifetime requirements of EN ISO 22153. Detailed information can be provided on request.	
Sound pressure level	< 72 dB (A)	
Further information		
EU Directives	Machinery Directive 2006/42/EC Low Voltage Directive 2014/35/EU EMC Directive 2014/30/EU RoHS Directive 2011/65/EU	
Reference documents	Dimensions SQV 05.2 – SQV 14.2/SQVRV 05.2 – SQVRV 14.2 with ACV 01.2 Electrical data SQV 07.2 – SQV 16.2 Technical data ACV 01.2	