# Data sheet

valid from: 3/27/25



**Type 2551 Magmeter; 4-20 mA Output**
**Wet-Tap/Mount/Use with Type 3519 wet tap valve**

**Model:**

- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Operating range: 0.05 to10 m/s, 0.15 to 33 ft/s
- Max pressure rating:
- 6.9 bar (100 psi) @ 0 °C (32 °F)
- 1.4 bar (20 psi) @ 65 °C (149 °F)
- Power source:
- 4 to 20 mA: 24 VDC ±10%, regulated, 22.1 mA max.
- Compatibility: 9900, 9900-1BC, 9950

**Flow:**

- *Only Signet installation fittings

| Communication | MFR # | Body | Electrode | Pipe Size (inch) | Code |
|---|---|---|---|---|---|
| 4-20 mA Output | 3-2551-V3-12 | PVDF | Hastelloy C | 0.5 - 4.0 | **159 002 209** |
| 4-20 mA Output | 3-2551-V4-12 | PVDF | Hastelloy C | 5.0 - 8.0 | **159 002 215** |
| 4-20 mA Output | 3-2551-V5-12 | PVDF | Hastelloy C | 10.0 - 36.0 | **159 002 221** |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com