CDX
Conventional

YBN-R/6

Conventional Electronics Free Mounting Base

Features

- Integral remote indicator output
- Low profile, only 8 mm
- Rugged design and electronics free
- Quick connections via square cable clamps
- Accepts 2.5 mm^2 cables
- Bayonet slot, low insertion force for detectors
- Available in white, ivory or black.





Description

Model YBN-R/6 is a Conventional Detector Mounting Base associated with the CDX Range of Detectors and is fully compatible with the majority of existing conventional fire alarm control panels.

It is supplied with square cable clamps for secure and reliable cable termination but the base does not provide line continuity during detector removal, therefore if Call Points are being used then these should be wired onto the zone first. The integrated third terminal provides remote indicator output.

Specification	
Ordering codes	YBN-R/6, YBN-R/6(WHT) or YBN-R/6(BLK)
Operating voltage	9.5 - 30 VDC
Operating temperature range	-10 °C to + 50 °C
Storage temperature range	-30 °C to + 60 °C
Maximum humidity	95% RH - non-condensing (at 40°C)
Colour / material	White, ivory or black / ABS
Weight (g) / Diameter (mm) / Height (mm)	51 / 100 / 8
Fixing centres (mm)	48 ~ 74

For further information visit our website.
Hochiki reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki to be a complete and up-to-date description. Check online for current version.