



ADVANTAGES

- Strong and airtight frame
- Most convenient handling
- Optimized for Bag-in Bag-out safe change
- For very high velocity (up to 3,5 m/s)
- Lightest V-bank steel box filter in the industry

Application	Compact fine filter for air handling systems with high airflows
Frame	Galvanised steel
Gasket	Polyurethane
Media	Glass fiber
Separator	Hot-melt
Sealant	Polyurethane
Rec. final pressure drop acc. EN 13053	Initial pressure drop + 100 Pa or initial pressure drop x3 (whichever is lower)
Max airflow	1,1 x nominal flow
Max Temperature (°C)	70°C
Relative Humidity max	100%

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow (m3/hr)	Pressure drop (Pa)	Media area (m²)	Weight (kg)
OPE-1070-610x305x292-P0-1HW	M6	ePM10 70%	610x305x292	2050	100	10.9	6
OPE-1070-610x610x292-P0-2HH	M6	ePM10 70%	610x610x292	4500	100	22.0	9
OPE-0155-610x305x292-P0-1HW	F7	ePM1 55%	610x305x292	2050	110	10.9	6
OPE-0155-610x610x292-P0-2HH	F7	ePM1 55%	610x610x292	4500	110	22.0	9
OPE-0170-610x305x292-P0-1HW	F8	ePM1 70%	610x305x292	2050	120	10.9	6
OPE-0170-610x610x292-P0-2HH	F8	ePM1 70%	610x610x292	4500	120	22.0	9
OPE-0180-610x305x292-P0-1HW	F9	ePM1 80%	610x305x292	2050	130	10.9	6
OPE-0180-610x610x292-P0-2HH	F9	ePM1 80%	610x610x292	4500	130	22.0	9