TRU Round stock grabs

Working load limit (WLL) 100 - 4000 kg

The TRU roundstock grab picks up roundstock and pipe material up to 600 mm in diameter quickly and safely. With its optional protective lining, it can also pick up materials with sensitive surfaces.

Product group: I4

INFO

For grabs fitted with a protective lining, it is important that all surfaces are dry, clean and free of oil and grease.

Shackle not supplied.

Technical data TRU

Model	Art.-No. standard	Art.-No. with protective lining	*WLL kg	Jaw capacity mm	*Weight kg
TRU100	N51902711	N51902712	100	50 - 150	3.9
TRU500	N51902701	N51902706	500	35 - 200	13.6
TRU1000	N51902702	N51902707	1000	35 - 200	13.6
TRU1500	N51902703	N51902708	1500	80 - 300	27.0
TRU3000	N51902704	N51902709	3000	80 - 300	49.0
TRU4000	N51902705	N51902710	4000	200 - 600	208.0

*NB: When fitted with rubber lining jaw capacity will be reduced by approx. 4 mm.

Dimensions TRU

Model	TRU 100	TRU 500	TRU 1000	TRU 1500	TRU 3000	TRU 4000
A, mm	270	503	509	720	740	1420
B min., mm	292	417	437	520	582	930
B max., mm	458	723	745	937	960	1815
C, mm	97	150	178	204	220	318
D, mm	43	56	82	84	125	205
E, mm	8	15	15	20	20	30
F, mm	17	17	30	25	30	35