

IR PLUS

Infrared Gas Detector with Intelligent Heated Optics

A dual beam infrared hydrocarbon detector providing real-time, fail-safe detection and exceptional reliability in harsh environments.



IR Plus is a dependable, durable, and exceptionally sturdy dual-beam infrared hydrocarbon gas detector. With optional display capabilities, this device ensures swift and fail-safe detection of methane, propane, and various other hydrocarbon further enhances its reliability, making it an ideal choice for demanding environments.



Industry Leading Warranty

With its industry leading 5 year warranty, IR Plus offers peace of mind and reduced maintenance costs.



Fast Response Time

With a response time of just 4 seconds, IR Plus gives you the information you need fast.



Intelligent Heated Mirror

Heated optical components combined with Stay-clIR coating ensures reliable performance in high temperature and humidity conditions.



High Stability in Harsh Conditions

IR Plus outperforms its nearest competitors when operating under high temperature and humidity conditions.



Remote Non-Intrusive Testing

Easily test on-site with options for Fixed Display, Remote Display (up to 3m), and local-HART.

Multiple Outputs

Standard 4-20 mA analogue and RS-485 (Modbus) outputs, plus Local-HART & HART over 4-20 mA options.



MOUNTING OPTIONS

	Wall Mount
	Pipe Mount
	Duct Mount
	Junction Box

DISPLAY OPTIONS

	No Display
	Fixed Display
	IS Barrier
	IS Barrier with Remote Display

SPECIFICATIONS

DEVICE SPECIFICATIONS	
GASES	Hydrocarbon (software-configurable to target gas), Methane, Propane, Ethylene, Hexane*, Butane* Contact Crowcon for more target gases
SIZE	194mm x 119mm x 94.2mm (7.6 x 4.7 x 3.7 ins)
WEIGHT	4.1kg (9.0lbs) IR Plus 4.5kg (9.92lbs) IR Plus with Fixed IR Display 4.9kg (10.8 lbs) IR Plus with IS Barrier Module 0.2kg (0.4 lbs) IR Plus Remote Display
ENCLOSURE MATERIAL	316L Stainless Steel
RESPONSE TIME (T90)	4 seconds
PERFORMANCE	Zero Drift: ±2% FSD per year Repeatability: ±2% FSD Linearity: ±2% FSD
IR SOURCE	Intelligent heated optics with Stay-clIR hydrophobic mirror
OPERATING VOLTAGE	12v DC to 30v DC
POWER	5.5 W (maximum; with heater on)
OUTPUT	3-wire 4-20 mA (Sink or Source) 2mA dirty optics warning (at 75% obscuration, configurable) 0mA detector fault signal (at 90% obscuration, configurable) RS-485 Modbus HART 7 (optional)
FAULT SIGNAL	<3.6 mA and/or >21mA
CONNECTION/PORT ENTRIES	2 x M20 or 2 x ¾"NPT cable gland entry
OPERATING TEMPERATURE	-40°C to +70°C (-40°F to 158°F)
OPERATING HUMIDITY	0 to 100% RH including condensing environments
DEGREE OF PROTECTION	IP66 (EN60529)
FUNCTIONAL SAFETY	IEC 61508, EN 50402, SIL2
PERFORMANCE STANDARDS	IEC EN 60079-26-1, FM 6310, FM 6320, ANSI/FM/UL 60079-29-1 (R2023)
HAZLOC STANDARDS	EN IEC 60079-0, EN/IEC 60079-1, EN/IEC 60079-11, EN/IEC 60079-31, FM 3810, ANSI/UL 60079-0(R2024), ANSI/UL 60079-1(R2024), ANSI/UL 60079-11, ANSI/UL 60079-31, ANSI/UL 61010-1
APPROVALS	ATEX, IECEx, INMETRO, CCC, PESO, ECAS, FM
EMC COMPLIANCE	EN50270, FCC CFR47 Part 15B, ICES-003
WARRANTY	5 years

*Pending

Disclaimer

Due to ongoing research and product improvement, specifications are subject to change without notice. While every effort has been made to ensure accuracy in this document, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This document is not intended to form the basis of a contract.

For more information:

t: +44 (0)1235 557700
e: info@crowcon.com
w: www.crowcon.com

Locate your Regional Sales Representative at:
www.crowcon.com/contact-us/where-to-buy

© 2026 Crowcon Detection Instruments Ltd.