Specifications



Photo is representative





Eaton 290168

Eaton Moeller® series ZB Overload relay, ZB12, Ir= 12 - 16 A, 1 N/O, 1 N/C, Direct mounting, IP20

General specifications	
PRODUCT NAME	Eaton Moeller® series ZB Thermal overload relay
CATALOG NUMBER	290168
MODEL CODE	ZB12-16
EAN	4015082901684
PRODUCT LENGTH/DEPTH	88 mm
PRODUCT HEIGHT	67 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.145 kg
CERTIFICATIONS	CE CSA-C22.2 No. 60947-4-1-14 UL Category Control No.: NKCR IEC/EN 60947-4-1 CSA File No.: 012528 UL UL File No.: E29184 CSA IEC/EN 60947 UL 60947-4-1 CSA Class No.: 3211-03 VDE 0660

Contacts

NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.

10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	5.4 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	1.8 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	16 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Electrical rating

CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	6 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 120 V	1.5 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	1.5 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	0.9 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.4 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.2 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	0.9 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	0.75 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V
SAFE ISOLATION	440 V AC, Between main circuits, According to EN 61140 240 V AC, Between auxiliary contacts, According to EN 61140 440 V, Between auxiliary contacts and main contacts, According to EN 61140
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	R300, DC operated (UL/CSA) B600 at opposite polarity, AC operated (UL/CSA) B300 at opposite polarity, AC operated (UL/CSA)
VOLTAGE RATING - MAX	600 VAC

Features & functions

FEATURES	Test/off button Trip-free release Reset pushbutton manual/auto Phase-failure sensitivity (according to IEC/EN 60947, VDE 0660 Part 102)

General information

AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
CLASS	CLASS 10 A / IEC 60947-4-1, 8.2.1.5.1.1. c) 4 min
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
DEGREE OF PROTECTION	IP00
FRAME SIZE	ZB12
MOUNTING METHOD	Direct mounting
OVERLOAD RELEASE CURRENT SETTING - MAX	16 A
OVERLOAD RELEASE CURRENT SETTING - MIN	12 A
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Overload relay ZB up to 150 A
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC 4000 V (auxiliary and control circuits)
SHOCK RESISTANCE	10 g, Mechanical, Sinusoidal, Shock duration 10 ms
SUITABLE FOR	Branch circuits, (UL/CSA)
TEMPERATURE COMPENSATION	Continuous ≤ 0.25 %/K, residual error for T > 40°

Short-circuit rating

SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)	100 kA, Fuse, SCCR (UL/CSA) 30 A, Class J/CC, max. Fuse, SCCR (UL/CSA)
SHORT-CIRCUIT PROTECTION RATING	25 A gG/gL, Fuse, Type “2” coordination Max. 6 A gG/gL, fuse, Without welding, Auxiliary and control circuits 50 A gG/gL, Fuse, Type “1” coordination Information on Type "1" and Type"2" coordination applies to 100 kA and 690 V

Terminal capacities

SCREW SIZE	M4, Terminal screw M3.5, Terminal screw, Control circuit cables
SCREWDRIVER SIZE	2, Terminal screw, Pozidriv screwdriver 1 x 6 mm, Terminal screw, Standard screwdriver
STRIPPING LENGTH (CONTROL CIRCUIT CABLE)	8 mm
STRIPPING LENGTH (MAIN CABLE)	10 mm
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (0.75 - 2.5) mm², Control circuit cables 2 x (1 - 4) mm², Main cables 2 x (0.75 - 2.5) mm², Control circuit cables 1 x (1 - 4) mm², Main cables
TERMINAL CAPACITY (SOLID)	2 x (0.75 - 4) mm², Control circuit cables 2 x (1 - 6) mm², Main cables 1 x (1 - 6) mm², Main cables 1 x (0.75 - 4) mm², Control circuit cables
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 8, Main cables 2 x (18 - 14), Control circuit cables
TIGHTENING TORQUE	1.8 Nm, Screw terminals, Main cables 1.2 Nm, Screw terminals, Control circuit cables

Resources

CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-tripping-zb-overload-relay-characteristic-curve-002.eps eaton-tripping-devices-zb-overload-relay-characteristic-curve-002.eps
DECLARATIONS OF CONFORMITY	eaton-thermal-overload-relay-declaration-of-conformity-uk251269en.pdf eaton-thermal-overload-relay-declaration-of-conformity-eu250786en.pdf
DRAWINGS	eaton-tripping-devices-overload-relay-zb-overload-relay-dimensions-003.eps eaton-tripping-devices-overload-relay-zb-overload-relay-3d-drawing.eps
ECAD MODEL	ETN.ZB12-16
INSTALLATION INSTRUCTIONS	eaton-overload-relays-zb12-zb32-il03407015z.pdf IL03407195Z
MCAD MODEL	DA-CS-zb12
PEP ECO-PASSPORT	eaton-thermal-overload-relays-pep-eato-00458-v0101-en.pdf
SALES NOTES	eaton-dol-3phase-ac-motor-starter-ms-16a-flyer-fl034009en-en-us.pdf
WIRING DIAGRAMS	eaton-tripping-devices-overload-relay-zb-overload-relay-wiring-diagram-002.eps

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.