

TBE-330 TIG Brush Specifications



Model Designation: TIG Brush TBE-330
Market Location: All regions except AUS/NZ

Features	Details
Case Design	330 Series Injection Moulded IP64
Case Material	PC/ABS
Case Colour	Yellow
Dimensions	245W x 190D x 370H
Weight	7.5kg
Mains Voltage	120VAC - 230VAC +5%/-10%, single phase
Input Current	2-4 amps (average)
Operating Environment	-30 °C to +45 °C (-22F to 113F)
Duty Cycle	Rated for continuous use at an ambient temperature of 30 degrees Centigrade, on any Mode setting.
Power Switch	Rotary Switch Off/On
Power Output	Rotary Switch
Low	9v AC
High	14v AC
Power Supply	Dynamic Power Transfer - 300VA
Maximum Operating Output Current	60A
Overload Control	Electronic
Applicator Tool Options	1. Classic Handle Cable & LokWand (Brush Connection - Push-In Brush) ¹ 2. Slimline PROPEL Torch (Brush Connection - Push-In Brush) ² 3. Compatible with all previous TIG Brush application tools ³
Cables (2)	Red EPDM insulated 4 metre with Handle Black EPDM insulated 4 metre with Clamp
Maximum Brush Size	Single
Standards Compliance	CE, C-Tick N22274

Note: Ensitech reserves the right to update product specifications at any time without notice.

¹Sold with 330 LokWand Kit
²Sold with 330 Slimline Kit
³Sold as separate attachments