

TBE-700 TIG Brush Specifications



Model Designation: TIG Brush TBE-700
Market Location: All regions except AUS/NZ

Features	Details
Case Design	700 Series Injection Moulded IP64
Case Material	PC/ABS
Case Colour	Purple
Dimensions	245W x 190D x 370H
Weight	12kg
Mains Voltage	120VAC - 230VAC +5%/-10%, single phase
Input Current	Average of 8 amps
Operating Environment	-30 °C to +45 °C (-22F to 113F)
Duty Cycle	Rated for continuous use at an ambient temperature of 30 degrees Centigrade (86F), on any Mode and Power setting.
Application Selection	Rotary Switch
Applications	Standby
	Single Brush 18V
	PROPEL™ / Wide 13V
Mode Selection	Rotary Switch
Mode Settings	Clean
	Polish / Engrave
	Print
Power Supply	Dynamic Power Transfer - 700VA
Maximum Operating Output Current	100A
Overload Control	Smart Circuit
Applicator Tool Options	1. Classic Handle Cable & Wand (M6 Brush)
	2. Classic Handle Cable & LokWand (Push-In Brush)
	3. PROPEL Torch (PROPEL Brush)
	4. Slimline PROPEL (Push-In Brush)
	5. Flexi Handle, Classic Handle Cable & Flexi Wand (5/16" Brush)
Cables (2)	Red EPDM insulated 4 metre with Handle
	Black EPDM insulated 4 metre with Clamp
Maximum Brush Size	Quad
Standards Compliance	CE, C-Tick N22274

Note: Ensitech reserves the right to update product specifications at any time without notice.