



Description Interruttore automatico scatolato

Code MSX 160c

No. of poles 3P

Rated current 160 A

Release Electromechanic

ELECTRICAL CHARACTERISTICS


Standard	IEC/EN 60947-2	Execution	Fixed
Use category	A	DIN rail mounting	Yes, by means of accessory
Rated frequency (Hz)	50 / 60	Can be equipped with motor operator	No
Rated operating voltage (Ue)	525 V ac - 250 V dc	Compatible interlock	-
Rated impulse withstand voltage (Uimp)	8 kV	Terminals supplied	Front FC
Overvoltage category	IV	Assembly position	Any
Insulation voltage (Ui)	690 V	Upline/downline power supply	Yes
Thermal regulation	0.63 - 0.8 - 1 x In	Electrical life (415Vac)	10.000 cycles
Magnetic regulation	Fixed - 1.600 A	Mechanical life	20.000 cycles
Neutral protection	-	Operating temperature	-5°C +65°C
Total power loss	46.2 W	Storing temperature	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Weight (kg)	0.8
Rated short-time withstand current for 0,3s (Icw)	-	Width	75 mm
I _{dn} regulation	-	Height	130 mm
DT regulation	-	Depth	68 mm

SERVICE BREAKING CAPACITY (ICU)

220/240Vac	35 kA	220/240Vac	18 kA
400/415Vac	25 kA	400/415Vac	13 kA
440Vac	15 kA	440Vac	7.5 kA
525Vac	7.5 kA	525Vac	4 kA
690Vac	-	690Vac	-
250Vdc	20 kA	250Vdc	10 kA

RATED BREAKING CAPACITIY (ICS)

DIMENSIONAL



STANDARDS/APPROVALS

