Product Datasheet
CD440B



CD440B

RCCB 4P 40A 30mA AC Class

Technical Features

Architecture	
Type of pole	3P+N
Number of poles	4
Electric current	
Rated current IN	40 A
Rated residual operating current Idn	30 mA
Breaking and opening capacity Idm	0.63 kA
Rated conditional short-circuit current Inc according to EN61008-1	10 kA
Rated current at -25°C	40 A
Rated current at -20°C	40 A
Rated current at -15°C	40 A
Rated current at -10°C	40 A
Rated current at -5°C	40 A
Rated current at 0°C	40 A
Rated current at 5°C	40 A
Rated current at 10°C	40 A
Rated current at 15°C	40 A
Rated current at 20°C	40 A
Rated current at 25°C	40 A
Rated current at 30°C	40 A
Rated current at 35°C	40 A
Rated current at 40°C	40 A
Rated current at 45°C	40 A
Rated current at 50°C	40 A
Rated current at 55°C	40 A
Rated current at 60°C	40 A
Rated current at 65°C	40 A
Rated current at 70°C	40 A
Installation, mounting	
Nominal tightening torque top terminal	2.80 - 2.80 Nm
Nominal tightening torque down terminal	2.80 - 2.80 Nm
Connectivity	
Type of connection	Screw terminal
Voltage	
Rated operational voltage Ue	230 - 400 V
Type voltage supply	AC
Rated insulation voltage Ui	500 V
Rated impulse withstand voltage Uimp	4000 V
Max. operating voltage	440 V
Frequency	
Frequency	50 - 50 Hz
Capacity	
Number of modules	4
Compatibility	
Suitable for DIN Rail	Yes
Safety	
Residual current type	AC
Ingress Protection (IP) class	IP20
Installation, mounting	
Type of top connection for modular devices	Screw terminal

Installation, mounting	
Type of bottom connection for modular devices	biconnect
Nominal tightening torque	2.80 - 2.80 Nm
Connection	
Cross-section of output with screws, for massive conductors	1 - 25 mm^2
Cross-section of output with screws, for flexible conductors	1 - 16 mm^2
Cross-section flexible conductor	16 mm^2
Cross-section rigid conductor	25 mm^2
Cross-section of input and output with screws, for flexible conductors	1 - 16 mm^2
Cross-section of input and output with screws, for massive conductors	1 - 25 mm^2
Power	
Power dissipation at IN	6.50 W
Use conditions	
Max. altitude	2000 m
Operating temperature	-25 - 40 °C
Endurance	
Electric endurance in number of cycles	2000
Number of mechanical operations	4000
Connectivity	
Top connection alignment for modular devices	Aligned terminal
Down connection alignment for modular devices	Aligned terminal
Dimensions	
Height	83 mm
Width	70 mm
Depth	70 mm
Sustainability	
RoHS conform	Yes