Product Datasheet
SBN232



SBN232

2-pole, 32A Modular Switch

Technical Features

Architecture	
Number of poles	2
Control/operation element	Break switch
Type of pole	2P
Electric current	
Rated current IN	32 A
Acceptable current rating AC21 category A	32 A
Acceptable current rating AC21 category B	32 A
Acceptable current rating AC22 category A	32 A
Acceptable current rating AC22 category B	32 A
Rated short-circuit making capacity Icm under 240 V AC according to IEC 60947-3	0.67 kA
Rated short-time withstand current Icw 1s IEC 60947	0.48 kA
Rated conditional short-circuit current Inc with fuse according to IEC/EN 60669-2-4	3000A/50A gG
Installation, mounting	
Nominal tightening torque	1.80 - 1.80 Nm
Voltage	
Rated operational voltage Ue	230 - 230 V
Installation, mounting	
Suitable for outdoor usage	No
Voltage	
Type voltage supply	AC
Rated insulation voltage Ui	440 V
Installation, mounting	
Type of bottom connection for modular devices	Screw terminal
Voltage	
Rated impulse withstand voltage Uimp	4000 V
Capacity	
Number of modules	1
Safety	
Ingress Protection (IP) class	IP20
Frequency	
Frequency	50 - 60 Hz
Dimensions	
Height	83 mm
Width	17.50 mm
Depth	68 mm
Dimensions	83 x 17.50 mm
Equipment	
Number of NO contacts	2
Number of NC contacts	0
Use conditions	
Operating temperature	-20 - 70 °C
Storage/transport temperature	-40 - 80 °C
Connection	
Cross-section flexible conductor	1.5 - 10 mm^2
Cross-section rigid conductor	1.5 - 16 mm^2

Endurance	
Number of mechanical operations	200000
Electrical durability at nominal load in AC21 in operating cycles	25000
Electrical durability at nominal load in AC22 in operating cycles	25000

Power	
Power dissipation at IN	3 W
Power loss per pole at In	1.50 W

Connectivity	
Down connection alignment for modular devices	Shifted terminal
Top connection alignment for modular devices	Shifted terminal

Compatibility	
Suitable for DIN Rail	Yes

Sustainability	
REACh-SVHC free	Yes
RoHS conform	Yes