ATL500

AUTOMATIC TRANSFER SWITCH CONTROLLER WITH NFC TECHNOLOGY AND SYNOPTIC, FOR 2 POWER SOURCES, (144X144MM/5.7X5.7”), SELF-SEEKING POWER SUPPLY 110...240VAC



Product designation			Automatic transfer switch controller for 2 power sources, self-powered, three phase control, with NFC and synoptic
Product type designation			ATL500
General characteristics			
Number of controlled power sources		Nr.	2
Display			No
Expandability			No
AC Power supply			
Rated supply voltage AC		VAC	110...240
Operating supply voltage range AC		VAC	90...300VAC L-N
Rated frequency		Hz	50/60
Operating frequency range		Hz	45...66
Immunity time for microbreakings			
	110VAC	ms	≤200
	220VAC	ms	≤400
Power consumption AC (Max)		VA	3.7
Voltage inputs			
Maximum rated voltage Ue			415VAC L-L (240VAC L-N)
Measurement range		V	155...519VAC L-L (90...300VAC L-N)
Frequency range		Hz	45...66
Measurement method			True root mean square (TRMS)
Input impedance			
	phase-phase		>1.0MΩ
	phase-neutral		>0.5MΩ
Measuring accurancy			±0.25% f.s.
Wiring mode			Single-phase, two-phase, three-phase with neutral system
Digital inputs			
Number of digital input		Nr.	2
Type of digital input			Negative
Digital current inputs		mA	≤5mA
Low input signal		VDC	≤2.6V
High input signal		VDC	≥3.1V
Input signal delay		ms	≥50


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

ATL500

AUTOMATIC TRANSFER SWITCH CONTROLLER WITH NFC TECHNOLOGY AND SYNOPTIC, FOR 2 POWER SOURCES, (144X144MM/5.7X5.7”), SELF-SEEKING POWER SUPPLY 110...240VAC


Relay outputs				
Number of relay output			Nr.	3
Contact arrangement				2 x 1NO-SPST (OUT1, OUT2) + 1 x C/O-SPDT (OUT3)
Electrical life			cycles	10^5
Mechanical life			cycles	10^7
Interface				
NFC interf.				Yes
Functions				
Programmable source type				Single-phase, two-phase, three-phase with neutral
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-30
		max	°C	+70
	Storage temperature			
		min	°C	-30
		max	°C	+80
Relative humidity			%	<80%
Maximum Pollution degree				2
Overvoltage category				3
Measurement category				III
Climatic sequence				Z/ABDM (IEC/EN 60068-2-61)
Shock resistance				15g (IEC/EN 60068-2-27)
Vibration resistance				0.7g (IEC/EN 60068-2-6)
Housing				
Execution				Flush mount
Material				Polycarbonate
Mounting				Flush mount - panel cut-out 138x138 mm
Degree of protection				IP40 on front, IP65 with optional gasket code EXP8001, IP20 on terminals
Dimensions (W x H x D)			mm	144 x 144 x 52.2mm
Weight			g	580
Dimensions				

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding




Wiring diagrams

Control of contactors - three-phase connection



Control of motorized changeover switch



Certifications and compliance

Compliance

	IEC/EN 60947-1
	IEC/EN 60947-6-1
	IEC/EN 61000-6-2
	IEC/EN 61000-6-3
	IEC/EN 61010-1
	IEC/EN 61010-2-030

Certificates

RCM

ETIM classification

ETIM 8.0

EC000236 - PLC CPU-module

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding