DMED330

ENERGY METER, THREE-PHASE WITH OR WITHOUT NEUTRAL, NON EXPANDABLE, CONNECTION BY CT /5A SECONDARY, 4U, RS485 INTERFACE, MULTI-MEASUREMENTS




Product designation			Three-phase energy meters
Product type designation			DMED330
Type			Three-phase with and without neutral
DIN rail module number			4
Auxiliary supply Us			
Operational frequency			
	min	Hz	50
	max	Hz	60
Power consumption			
	Max	VA	3.5
Power dissipation Max		W	2.7
Measuring voltage inputs			
Rated voltage (Ue)			
	phase-phase	VAC	380…415
	phase-neutral	VAC	220…240
Operating voltage range			
	phase-phase	VAC	323…456
	phase-neutral	VAC	187…264
Connection method			Via CT
Current			
IEC maximum (Imax)		A	5
IEC minimum (Imin)		A	0.05
IEC rated (Iref-lb)		A	5
IEC start (Ist)		mA	0.005
Transition (Itr)		A	0.25
Accuracy			
	Active energy		Class 0.5s (IEC/EN 62053-22)
	Reactive energy		Class 2 (IEC/EN 62053-23)
Output characteristics			
LED Pulse rate		pulse/kWh	1000
LED Pulse duration		ms	30
Insulations			
Rated insulation voltage Ui IEC/EN		V	250
Rated impulse withstand voltage Uimp		kV	6
Operating frequency withstand voltage		kV	4
Mechanical features			
Housing type			Polyamide
Terminals type			Fixed
Conductor cross section			
	min	mm²	0.2

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

		Max	mm²	4 for supply voltage measurement; 2.5 for current measurement
		min	AWG	24
		Max	AWG	12
Tightening torque (Max)				
			Nm	0.8
			lbin	7
Fixing				Din rail
Weight			g	332
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+55
	Storage temperature			
		min	°C	-25
		max	°C	+70
Relative humidity			%	<80
Maximum Pollution degree				2

Dimensions




Wiring diagrams

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding


DMED330

ENERGY METER, THREE-PHASE WITH OR WITHOUT NEUTRAL, NON EXPANDABLE, CONNECTION BY CT /5A SECONDARY, 4U, RS485 INTERFACE, MULTI-MEASUREMENTS


Single-phase




Two-phase



Three-phase with or without neutral



Three-phase without neutral in ARON connection




Tariff input

100...240VAC




Pulse output 30VDC 50mA for DME D305 T2



RS485 for DME D330



M-Bus for DME D332



Certifications and compliance

Compliance

	IEC/EN 50470-1
	IEC/EN 61010-1
	IEC/EN 61010-2-030

Certificates

	EAC
	RCM

ETIM classification

ETIM 8.0	EC001506 - Kilowatt-hour meter

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding