Handling protection

ULTRANE 551

Unbeatable for fingertip precision

EN 388

4131X

Dexterity EN ISO 21420: 5/5

CATEGORY 2

OEKO TEX® STANDARD 100 CQ 979/2 IFTH

SPECIFIC ADVANTAGES

Comfort

- Great dexterity, due to the gloves reduced thickness
- Added comfort, due to the seamless knit lining Absorption of perspiration ensured by the cellular structure of the polyurethane

Durability

- Suitable for long-term wear : excellent abrasion resistance

Skin protection

- Free of harmful substances: OEKO-TEX® STANDARD 100
- Contains traces of DMF in compliance with occupational exposure limits

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

INDUSTRIES

- Automotive industry
- Construction industry: Carpenters/Joiners
- Construction industry: Heating engineers/Plumbers
- Construction industry: Metalworkers/Locksmiths
- Electronics
- Food industry
- HEALTH CARE: Cosmetic industry
- HEALTH CARE: Pharmaceutical industry

APPLICATIONS

- Fitting small screws and fasteners
- Laying wood, panelling or moudling
- Maintaining pipes, heating equipment
- Installing and repairing locks
- High-frequency antennae riveting
- Microprocessor handling
- Sorting small parts
- Electronic component assembly (displays, LEDs, etc.)
- Packaging
- Cosmetics preparation

Edit 19/10/2026

Handling protection

ULTRANE 551

LEGENDS

EN388

MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

4	1	3	1	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	13
Exterior finish	Ventilated back
Material	Polyurethane
Cuff characteristic	Knitted Cuff
Colour	Grey
Length (cm)	21-27
Sizes	5 6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.3E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	6.3E+9 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 10 pairs/bag 100 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/05/23/0896
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 19/10/2026