



Meinberg Funkuhren

Lange Wand 9

31812 Bad Pyrmont, Germany

Phone: +49 (5281) 9309-0

Fax: +49 (5281) 9309-30

<https://www.meinbergglobal.com>

info@meinberg.de

LANTIME M500: Time and Frequency Synchronization in Rail Mount Chassis

Modular Time- and Frequency Synchronization System for Industrial Applications in DIN Rail Chassis

The full-featured DIN railmount package has one power supply slot, a clock module slot, a CPU slot and two slots for additional input and output modules. Both, wide range AC and a 20-60 V DC power supply model are available.

Key Features

- Synchronizes NTP-compatible clients with support for NTP, SNTP, and NTS - Network Time Security
- Optimized space usage
- Synchronization of NTP and SNTP compatible clients
- Web-based status and configuration interface and console-based graphical configuration utility
- IMS - Intelligent Modular System platform
- Up to 2 PTP (IEEE 1588-2008) modules
- Hot Plug
- Arbitrary combinations of modules
- Meinberg's LANTIME time server is available with a variety of additional output options: IRIG Time Code, frequency synthesizer and programmable pulse outputs illustrate some of the many expansion options for your NTP server
- Up to 8 additional LAN ports

Description

The M500 railmount chassis offers the following slot types:

- * IMS-PWR High efficiency power supply (AC and DC versions available)
- * IMS-CLK Reference clock module
- * IMS-MRI IRIG, 1PPS, 10MHz input module:
- * IMS-ESI Input references for 2048kHz, 2.048MBit/s and variable frequencies:

MRI and ESI slots are also available for a variety of output signals:

Pulses, Frequencies, Time Codes, Serial time telegrams) and of course more network interfaces (IEEE-1588, NTP ports)

* IMS-CPU Central processor module providing NTP / SNTP time synchronization and management and configuration interfaces

* IMS-CES Expansion slot for Error output (standard configuration) and for further additional output signals (PPS, timecode...):

Rail Mount NTP Time Server for large Networks

With up to 6,000 NTP requests per second, the system is able to provide time for hundreds and thousands of NTP clients. The LANTIME module supports the following protocols: IPv4, IPv6, NTP / SNTP (v2, v3, v4), HTTP (S), SSH, Telnet, SNMP (v1, v2, v3), FTP, SFTP, DHCP/DHCPv6. For each system, up to 99 logical network interfaces are available (99 IPv4 and 99 IPv6 addresses).

Scalable NTP Time Server System

All modules are hot-plug capable and the modules can be configured via the central web interface (from the CPU module). Almost infinite number of combinations of input and output modules are available to meet almost any synchronization task. Because of simple extension by upgrading the system with new modules the scalability of the M500 system is ensured.

Slots for Input Signals:

IMS-MRI: Standard reference inputs

IMS-ESI: Extended reference inputs

Both of these reference input interfaces may also be used as I / O slot.

Front Panel

The front panel of LANTIME M500 integrates the familiar LC-Display with 4x16 characters and the well known LANTIME menu panel with 4 directional and 4 function buttons. This allows for a simple and fast on-site configuration of the main parameters. Hundreds of configuration options for the LANTIME CPU and the IMS input and output modules can be changed using the powerful web interface.

available IMS modules

Characteristics

Supported Reference Signals	The following reference sources can be used to synchronize the system: * GPS - Global Positioning System * GLONASS - Russian GNSS * GALILEO - European GNSS * BeiDou - Chinese GNSS * PZF - German DCF77 longwave radio signal * PTP/IEEE1588 - Precision Time Protocol * NTP - Network Time Protocol * SyncE - Synchronous Ethernet * Timecodes - IRIG/AFNOR timecodes (AM/DCLS) * PPS -Pulse Per Second * 10MHz - 10MHz reference frequency * 2.048kHz - 2.048kHz reference frequency * E1/T1 - Telecom Synchronization Input with full SSM/BOC support The priority of all input signals can be freely configured in addition to a bias value and a precision level specification for each source.
Status Indicators	Four bicolor LEDs showing status of: - reference time - time service - network - alarm

Display	LC Display, 4 x 16 characters
Control Elements	Eight push buttons to set up basic network parameters and to change system settings.
Frequency Outputs	Frequency Synthesizer for arbitrary frequencies between 0.125 Hz and 10 MHz, adjustable phase, output via external modules such as [1] IMS-BPE modules
Accuracy of Pulse Outputs	Depends on oscillator option: < ±50ns (OCXO SQ, OCXO MQ, OCXO HQ, OCXO DHQ, Rubidium)
Serial Time String Output	COM 0: Baudrate: 300, 600, 1200, 2400, 4800, 9600, 19200 Baud Data Format: 8E1, 8E2, 8N1, 8N2, 8O1, 7E1, 7E2, 7N2, 7O1, 7O2 Time Telegram: [2] Meinberg Standard Time String , SAT, NMEA RMC, Uni Erlangen (NTP), COMPUTIME, Sysplex, [3] Capture String , SPA, RACAL, Meinberg GPS, NMEA GGA, NMEA RMC GGA, NMEA ZDA, ION, 6021 or IRIG-J
Relay Outputs	Error Relay * Max. Switching Voltage: 125 V DC / 140 V AC * Max. Switching Current: 1 A * Max. Switching Power: 30 W DC / 60 VA AC * Response Time: Approx. 2 ms
Network Interface	Base Chassis: <u>CPU-C05F1</u> 1 x 10/100 MBit, RJ45 <u>CPU-C15G2</u> 1 x 100/1000BASE-T RJ45 1 x 1000BASE-T SFP Network Expansion - LNE Options: Up to 8 additional network interfaces (GbE Gigabit Support) with 10/100/1000 MBit RJ45 connector or 1000BASE-T SFP (Multimode / Singlemode).
Universal Serial Bus (USB) Ports	1x USB Port: - install firmware upgrades - backup and restore configuration files - copy security keys - lock/unlock front keys

Power Consumption	50 W max.
Operating Voltage	Maximum power range: AD10: 90 - 265 V AC, 47-63 Hz / 90-250 V DC DC20: 20 - 60 V DC DC10: 10 - 36 V DC
Form Factor	Aluminium housing for DIN mounting rail (black powder-coated)
CPU	CPU-C15G2 * Intel® Atom
Operating System of the SBC	GNU/Linux 4.x
Network Protocols OSI Layer 4 (Transport Layer)	TCP, UDP
Network Protocols OSI Layer 7 (Application Layer)	Telnet, FTP, SSH (including SFTP, SCP), HTTP, HTTPS, syslog, SNMP
Internet Protocol (IP)	IPv4, IPv6
Network Autoconfiguration Support	IPv4: Dynamic Host Configuration Protocol - DHCP (RFC 2131) IPv6: Dynamic Host Configuration Protocol - DHCPv6 (RFC 3315) and Autoconfiguration Networking - AUTOCONF (RFC 2462)
Network Time Protocol (NTP)	NTP v2 (RFC 1119), NTP v3 (RFC 1305), NTP v4 (RFC 5905) SNTP v3 (RFC 1769), SNTP v4 (RFC 4330) Symmetric key-based authentication using MD5, SHA-1, or AES-128-CMAC hashes NTP v4 Autokey (private/public key pairs)
Network Time Security (NTS)	As of LTOS version 7.08, all Meinberg IMS LANTIME time servers offer full support for NTS (Network Time Security) in unicast client/server mode.
Parallel Redundancy Protocol (PRP)	PRP (IEC 62439-3)
Time Protocol (TIME)	Time Protocol (RFC 868)
IEC 61850	Synchronization of IEC 61850-compliant devices using SNTP
Hypertext Transfer Protocol (HTTP)	HTTP/HTTPS (RFC 2616)
Secure Shell (SSH)	SSH v1.3, SSH v1.5, SSH v2 (OpenSSH)

Telnet	Telnet (RFC 854-RFC 861)
Simple Network Management Protocol (SNMP)	SNMPv1 (RFC 1157), SNMPv2c (RFC 1901-1908), SNMP v3 (RFC 3411-3418)
Physical Dimensions	118 mm x 193 mm (227 mm)* x 160 mm - width x height x depth * The sizes in brackets take into account the connections and module handles.
Supported Temperature	Operational: 0 - 50 °C (32 - 122 °F) Storage: -20 - 70 °C (-4 - 158 °F)
Supported Humidity	Max. 95 % (non condensing) at 40 °C (104 °F)
Technical Support	Meinberg offers free lifetime technical support via telephone or e-mail.
Warranty	Three-year warranty
Firmware Updates	Firmware is field-upgradeable, updates can be installed directly from the unit or via a remote network connection. Software updates are provided free of charge for the lifetime of your Meinberg product.
RoHS Status of Product	This product is fully RoHS-compliant.
WEEE Status of Product	This product is handled as a B2B (Business to Business) category product. To ensure that the product is disposed of in a WEEE-compliant fashion, it can be returned to the manufacturer. Any transportation expenses for returning this product (at end-of-life) must be covered by the end user, while Meinberg will bear the costs for the waste disposal itself.
Additional Information	Additional information about the Meinberg LANTIME family of NTP time servers and other LANTIME models can be found on the [4] LANTIME overview page .

Manual

There is no online manual available for this product.: [5][Contact us](#)

Links:

[1] <https://www.meinbergglobal.com/english/products/ims-output-modules.htm>

[2] <https://www.meinbergglobal.com/english/specs/timestr.htm>

[3] <https://www.meinbergglobal.com/english/specs/capstr.htm>

[4] <https://www.meinbergglobal.com/english/products/ntp-time-server.htm>

[5] <mailto:info@meinberg.de>