Product datasheet

Specifications



extension iETL iTL 16- 2P - 1C/O+1NO -16A - coil 110VDC - 230...240V AC 50/60Hz

A9C32816

Main

range of product	Acti9
Product or component type	Extension for impulse relay
Device short name	iETL iTL 16
Relay application	Remote control
Poles description	2P
Pole contact composition	1 C/O + 1 NO
[In] rated current	16 A
Network type	AC

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	415 V AC 50/60 Hz
Control type	Toggle Remote control
Control signal type	Impulse
Switching frequency	5 switching operations/minute
Impulse duration	50 ms
Remote control type	Illuminated push-button 3 mA
Local signalling	ON/OFF indication
[Uc] control circuit voltage	230...240 V AC 50/60 Hz 110 V DC
Supply inrush power	19 VA
Mounting mode	Fixed, on right side of TL
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	60 mm
Width	18 mm
Depth	84 mm
Colour	White
Electrical durability	AC-21: 200000 cycles AC-22: 100000 cycles
Connections - terminals	Tunnel type terminals - <= 6 mm²
Auxiliary connection terminal	Tunnel type terminals control circuit in 0.5…6 mm²

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Range compatibility	Acti9 iTL Acti9 iTLi
Product compatibility	ITL 16A

Environment

Standards	EN 669-1 EN 669-2-2
Product certifications	GOST
Quality labels	NF VDE CEBEC KEMA IMQ
Noise level	60 dB
IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	3
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-20…50 °C
Ambient air temperature for storage	-40…70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.900 cm
Package 1 Width	8.000 cm
Package 1 Length	9.500 cm
Package 1 Weight	123.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	8.700 cm
Package 2 Width	10.000 cm
Package 2 Length	26.700 cm
Package 2 Weight	1.035 kg
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	9.812 kg

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**6 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0.7 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**5 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.3 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**Yes**
SCIP Number	**6763a476-30bc-4d05-a4bb-93f8d65c3771**
EU RoHS Directive	Compliant
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
OECD PFAS Regulation	Item contains PFAS Chemicals
Ship Recycling Directive	Compliant
POP Directive	No POPs
Halogen-free status	**Halogen free plastic parts product**
PVC free	**Yes**
Silicone-free	**No**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**62**
End of life manual availability	**No need of specific recycling operations**

Take-back	**No**
WEEE Label	 **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**