Product datasheet

Specifications



iPF K 40 modular surge arrester - 1 pole + N - 340V

A9L15687

Main

Range of product	IPF K
range of product	Acti9
Product name	Acti9 iPF K
Product or component type	Surge arrester
Device short name	iPF K
Device application	Distribution
Standards	IEC 61643-11:2011
Product certifications	EAC CE
Poles description	1P + N
Remote signalling	Without
Surge arrester type	Electrical distribution network
Earthing system	TT TN-S

Complementary

Surge arrester class type	Type 2
Surge arrester technology	MOV + GDT
[Ue] rated operational voltage	230 V AC (+/- 10 %) at 50/60 Hz
Nominal discharge current	Common mode: 15 kA (L/PE) Common mode: 15 kA (N/PE) Differential mode: 15 kA (L/N)
Maximum discharge current	Common mode: 40 kA L/PE Common mode: 40 kA N/PE Differential mode: 40 kA L/N
[Uc] maximum continuous operating voltage	Common mode: 260 V N/PE Differential mode: 340 V L/N
Maximum [Up] voltage protection level	Common mode 1.5 kV type 2 N/PE Differential mode 1.5 kV type 2 L/N
[Ut] temporary overvoltage	337 V L/N 5 s withstand 442 V L/PE 5 s withstand 1200 V N/PE 200 ms withstand 1453 V L/PE 200 ms withstand
Disconnector device type	Associated circuit breaker iK60N 40 A curve C - Icu 6 kA Associated fuse gG 63 A - Icu 25 kA
Signalling circuit voltage	0.25 A/250 V AC 50/60 Hz
Mounting mode	Clip-on (DIN rail)

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

9 mm pitches	4
Height	81 mm
Width	36 mm
Depth	69 mm
Net weight	210 g
Colour	White (RAL 9003)
[Ipe] Ground residual current	0.003 mA
Connections - terminals	Tunnel type terminal (top or bottom) 25 mm² rigid Tunnel type terminal (top or bottom) 16 mm² flexible Tunnel type terminal (top or bottom) 16 mm² flexible with ferrule
Wire stripping length	11 mm
Tightening torque	3.5 N.m
Compatibility code	IPF K 40

Environment

IK degree of protection	IK03 conforming to IEC 62262
Relative humidity	5…95 %
Operating altitude	2000 m
Ambient air temperature for operation	-25…60 °C
Ambient air temperature for storage	-40…85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	7.500 cm
Package 1 Length	9.000 cm
Package 1 Weight	205.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	8.500 cm
Package 2 Width	9.500 cm
Package 2 Length	27.500 cm
Package 2 Weight	1.303 kg
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	15.802 kg

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	0bbc2178-3d34-4158-9394-3fac14d7c7ed
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
OECD PFAS Regulation	Item contains PFAS Chemicals
Ship Recycling Directive	Reportable
POP Directive	No POPs
Halogen-free status	Halogen free plastic parts product

Use Again

Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins