# Product datasheet

Specifications



## VTPN Distribution board, DBSeT, 36 module, 125A Modular incomer, IP41, Surface

DBV336MS

## Main

| | |
|---|---|
| **Range of the product** | DBSeT |
| **Product or component type** | Distribution board |
| **enclosure type** | Distribution enclosure |
| **Device application** | Low voltage electrical distribution |
| **Provided equipment** | earthing bar<br>pan assembly<br>neutral bar<br>enclosure |
| **Number of ways** | 36 ways (outgoer) |

## Complementary

| | |
|---|---|
| **[In] rated current** | 125 A |
| **[Icw] rated short-time withstand current** | 17 kA for 0.25 s |
| **[Ipk] rated peak withstand current** | 34 kA |
| **[Uimp] rated impulse withstand voltage** | 6 kV |
| **Rated voltage** | 240…415 V AC 50/60 Hz |
| **Network number of phases** | 3 phases |
| **[Ui] rated insulation voltage** | 500 V AC |
| **Protection device options** | Isolator (incomer)<br>Residual current circuit breaker (RCCB) (incomer)<br>Residual current circuit breaker with overcurrent protection (RCBO) (outgoer)<br>Miniature circuit breaker (MCB) (outgoer)<br>Isolator + residual current circuit breaker (RCCB) (incomer) |
| **Enclosure mounting** | Surface |
| **Door type** | Plain flat door |
| **Cable entry** | Removable gland plate at top and bottom of the enclosure |
| **Enclosure material** | Painted sheet steel 1.2 mm thick |
| **Colour** | White (RAL 9003) |
| **Width** | 425 mm |
| **Height** | 685 mm |
| **Depth** | 124.90 mm |

## Environment

| | |
|---|---|
| **IP degree of protection** | IP41 conforming to IEC 60529 |
| **IK degree of protection** | IK08 |

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Ambient air temperature for operation** | 50 °C |
| **Standards** | IEC 61439-3<br>IEC 61439-1 |
| **Product certifications** | DEKRA |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 13.6 cm |
| **Package 1 Width** | 44.5 cm |
| **Package 1 Length** | 70.5 cm |
| **Package 1 Weight** | 16.4 kg |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **180 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **78 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **5 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **3 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **55 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **40 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **Yes** |
| Packaging without single use plastic | **No** |
| EU RoHS Directive | **Compliant By Exemption** |
| REACh Regulation | **Reference contains Substances of Very High Concern above the threshold** |
| Halogen-free status | **Product contains halogen above thresholds** |
| PVC free | **Yes** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **96** |
| End of life manual availability | **No need of specific recycling operations** |
| Take-back | **No** |

Image of product / Alternate images

**Alternative**

