Product datasheet

Specifications



Easy9 switch disconnector - 3P - 125 A - 400 V

EZ9S16392

Main

Range	Easy9
Product or component type	Switch disconnector
Device short name	Easy9 switch
Switch application	Distribution
Poles	3P
Utilisation category	AC-22A
Suitability for isolation	Yes

Complementary

[Ie] rated operational current	125 A at 400 V 50/60 Hz
[Ue] rated operational voltage	400 V AC 50/60 Hz
[Icm] rated short-circuit making capacity	1.875 kA
[Icw] rated short-time withstand current	1.5 kA during 1 s
[Ui] rated insulation voltage	500 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	4 kV
Control type	Toggle
Local signalling	ON/OFF indication
Contact position indicator	Yes
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	81 mm
Width	54 mm
Depth	66.5 mm
Colour	Grey
Mechanical durability	7000 cycles
Electrical durability	1000 cycles
Connections - terminals	Tunnel type terminal (top or bottom) 1…50 mm² rigid Tunnel type terminal (top or bottom) 1…35 mm² flexible
Tightening torque	3.5 N.m

Environment

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	IEC 60947-3
Product certifications	CE
IP degree of protection	IP20 conforming to IEC 60529
Tropicalisation	2
Ambient air temperature for operation	-5…55 °C
Ambient air temperature for storage	-5…70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	8.000 cm
Package 1 Length	8.500 cm
Package 1 Weight	249.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	9.000 cm
Package 2 Width	9.000 cm
Package 2 Length	23.000 cm
Package 2 Weight	1.065 kg
Unit Type of Package 3	S03
Number of Units in Package 3	48
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	13.201 kg

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**49 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**4 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**44 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.5 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
SCIP Number	**0dbcf8b1-4732-4e36-88bc-462a078c2d4c**
EU RoHS Directive	Compliant
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	**Product contains halogen above thresholds**
PVC free	**Yes**

Use Again

Repack and remanufacture

Recyclability potential, in %	**42**
End of life manual availability	**No need of specific recycling operations**
Take-back	**No**