Product datasheet

Specifications



Easy UPS 1 Ph On-Line, 2000VA, Rackmount 2U, 230V, 4x IEC C13 outlets, Intelligent Card Slot, LCD, W/ rail kit

SRVS2KRIRK

To be discontinued

Discontinued on: 31 Oct 2026

To be end-of-service on: 30 Aug 2029

Overview

Presentation	For small to medium businesses, Easy UPS 1 Ph On-Line provides essential power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.

Main

Main input voltage	230 V AC 1 phase
Other input voltage	220 V 240 V
Input connection	IEC 60320 C14
Efficiency at full load	110...285 V half load 160...280 V full load
Input frequency	40...70 Hz auto sensing
Output voltage	230 V AC 1 phase
Other output voltage	220 V 240 V
Rated power in W	1600 W
Rated power in VA	2000 VA
Output connection	4 IEC 60320 C13
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Maximum configurable power in VA	2000 VA
Maximum configurable power in W	1600 W
UPS topology	On-Line
Waveform type	Sine wave
Efficiency	88 % (full load)
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	APCRBCV201

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Complementary

Battery type	Lead-acid internal included
Control panel	Multifunction LCD status and control console
Free slot	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	Serial port USB port Available expansion slot
Surge energy rating	600 J
Number of rack unit	2U
Cable length	1.48 m
Number of cables	1
Color	Black (RAL 7010)
Height	86 mm
Width	438 mm
Depth	462 mm
Product weight	19.0 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
USB compatible	Yes
Mounting position	Horizontal
Mounting mode	Rack-mounted with included kit
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Easy UPS 1Ph On-Line
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	CE UKCA
Standard	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0…40 °C
Ambient air temperature for storage	-20…50 °C
Storage altitude	0…15000 m
IP protection	IP20
Relative humidity	0…95 % non-condensing
Storage relative humidity	0…95 % non-condensing
Acoustic level	50 dBA

Operating altitude	0...3000 m

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	48 V
Extendable runtime	0
Included battery module	0
Empty battery slot	0
Typical recharge time	4 h
Battery life	3…5 year(s)
Battery charging power	76 W rated
Battery power in VAh	305 VAh runtime

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.000 cm
Package 1 Width	56.000 cm
Package 1 Length	79.000 cm
Package 1 Weight	20.702 kg

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**4 092 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**163 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**9 540 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
SCIP Number	**080b8d64-796e-42e7-a17d-31b86e55d143**
EU RoHS Directive	**Compliant By Exemption**

Use Again

Repack and remanufacture

Recyclability potential, in %	**65**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative





Product datasheet SRVS2KRIRK

