SICK.COM



DATA SHEET

CQ35-25NPP-KW1

CQ
Capacitive proximity sensors

SICK Sensor Intelligence



Illustration may differ

CAPACITIVE PROXIMITY SENSORS

CQ35-25NPP-KW1

ORDERING INFORMATION

Type	part no.
CQ35-25NPP-KW1	6020478

Further device versions and accessories at www.sick.com/CQ

DETAILED TECHNICAL DATA

FEATURES

Housing	Rectangular
Dimensions (W x H x D)	35 mm x 69.5 mm x 15 mm
Sensing range S_n	4 mm ... 25 mm
Safe sensing range S_a	18 mm
Installation type	Non-flush
Switching frequency	50 Hz
Connection type	Cable, 4-wire, 2 m [1]
Switching output	PNP
Switching output detail	PNP
Output function	Complementary
Electrical wiring	DC 4-wire
Adjustment Potentiometer	 Sensitivity (270°)
Enclosure rating	IP67 [2]
Items supplied	Screwdriver for potentiometer adjustment (1 x)

[1] Do not bend below 0 °C.

[2] According to EN 60529.

MECHANICS/ELECTRONICS

Supply voltage	10 V DC ... 36 V DC
Ripple	≤ 10 % [1]
Voltage drop	≤ 2.5 V DC [2]
Current consumption	10 mA [3]
Time delay before availability	≤ 100 ms
Hysteresis	4 % ... 20 %
Reproducibility	≤ 5 % [4] [5]
Temperature drift (of S_r)	± 10 %
EMC	According to EN 60947-5-2 [6]
Continuous current I_a	≤ 200 mA
Cable material	PVC
Conductor size	0.34 mm²
Short-circuit protection	✓
Power-up pulse protection	✓
Shock and vibration resistance	30 g, 11 ms / 10 ... 55 Hz, 1 mm
Ambient operating temperature	–25 °C ... +75 °C
Housing material	Plastic, PC
Sensing face material	Plastic
UL File No.	NRKH.E191603

[1] Of Ub.

[2] At I_a max.

[3] Without load.

[4] Of Sr.

[5] Supply voltage U_B and constant ambient temperature Ta.

[6] In EMC critical applications, conducted interference levels may lie within the frequency range of the oscillator. This can cause changes to the output signal. (See operating instructions.).

SAFETY-RELATED PARAMETERS

$MTTF_D$	897 years
DC_{avg}	0 %
T_M (mission time)	20 years

REDUCTION FACTORS

Note	The values are reference values which may vary
Metal	1
Water	1
PVC	Approx. 0.4
Oil	Approx. 0.25
Glass	0.6
Ceramics	0.5
Alcohol	0.7
Wood	0.2 ... 0.7

INSTALLATION NOTE


Remark	Associated graphic see "Installation"

A	35 mm
B	35 mm
F	6 x S_n (max. 150 mm)


CERTIFICATES

EU declaration of conformity	✓
UK declaration of conformity	✓
Moroccan declaration of conformity	✓
China RoHS	✓
China Compulsory Product Certification (CCC) exempt	✓
cULus certificate	✓


INSTALLATION NOTE




INSTALLATION NOTE




CONNECTION TYPE



CONNECTION DIAGRAM CD-005



DIMENSIONAL DRAWING CQ35, CABLE



Dimensions in mm (inch)
① Display LED
② Potentiometer
③ Connection

Further information as well as suitable accessories, example applications and downloads such as CAD dimensional models, operating instructions and software can be found at www.sick.com/6020478

SICK AG
WALDKIRCH
GERMANY
SICK.COM

SICK AT A GLANCE

SICK is a leading global technology company for intelligent sensors and integrated solutions in industrial automation. Our technologies set benchmarks, making your industrial processes more efficient, safer and more sustainable – both in logistics and manufacturing operations.

SICK combines sensor intelligence with industry expertise and certified consulting services. We provide the ideal foundation for scalable as well as tailor-made automation solutions and create added value along the entire value chain. Our close partnerships with our customers are more than just a promise: Together, we optimize productivity, improve quality, protect health and safety, and help build a sustainable future. All with empathy and trust.

Since 1946, we have been developing innovative technologies with passion and a pioneering spirit. With a global network in around 40 countries, SICK has a global presence and is always close by. The company's headquarters are located in Waldkirch near Freiburg, Germany. Our customers benefit from our understanding of both local and global requirements, which enables us to deliver tailor-made solutions

SICK

Sensor Intelligence