



TEGERA® CHEMFORCE 7350



[Learn more](#)

KEEP THE HEAT AND THE GRIP

Super soft, winter lined nitrile glove for freezer rooms or outdoor use. The sandy finish gives a perfect grip on slippery tools. The chemical protection layer is 0,3 mm. The glove is waterproof, oil and grease resistant and approved for handling foodstuffs. It has a good fit and is warm and comfortable.

CHARACTERISTICS

- High level of protection
- Durable
- Good grip
- Good fit
- Comfortable
- Warm

FUNCTIONS

- Protection against chemicals
- Approved for handling foodstuffs
- Latex-free
- Oil and grease resistant
- Water and oil repellent
- Waterproof

## PREVENTS RISK OF

Corrosive injuries, Contact with dirt, Contact with chemicals, Contact with damp, Contact with oil and fat, Contact with cold

## PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, Microbiological risk environments, Environments hazardous to health, Corrosive environments, Cold environments, Wet environments, Moist environments, Oily and greasy environments, Dirty environments

## PRIMARY AREAS OF USE

Painting, Construction, Concrete work, Marine work, Petro-chemical work, Paper industry work, Food handling, Chemical work, Chemical technology work

## PRIMARY INDUSTRIES OF USE

Oil and gas extraction, Chemical and petrochemical industry, Mining and quarrying

## TYPE OF WORK

Medium weight

## CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

## SPECIFICATION

**TYPE** Chemical protection gloves, Cold insulation gloves

**CATEGORY** Cat. III

**COLLECTION** Chemforce

**THICKNESS** 0,3\* mm (\*chem-layer)

**LINING** Winter-lined

**LINING MATERIAL** Fleece

**LENGTH** 300 mm

**DEXTERITY** 5

**GRIP DESIGN** Sandy finish

**COLOUR** Blue

**PAIRS PER: BUNDLE/CARTON** 5/60

**AQL** 1.5

**DISPLAY TYPE** Bag with euro slot

**DIPPING MATERIAL** Nitrile

**INNER MATERIAL SPECIFICATION** Acrylic

**MIDDLE MATERIAL SPECIFICATION** Cotton

**OUTER MATERIAL SPECIFICATION** Nitrile

## COMPLIANCE

**CE 0598**

TP TC 019:2011

**UK CA** Cat. III

EN ISO 21420:2020

**EAC**

EN 388:2016+A1:2018 3121X



EN ISO 374-5:2016



EN ISO 374-1:2016+A1:2018 Type B JKOPT



## FEATURES



Warm lining



Waterproof



Windproof



Chemical protection

## TEST ACCORDING TO EN ISO 374-1:2016

| Tested chemical  | J    | K    | O    | P     | T    |
|------------------|------|------|------|-------|------|
| Permeation level | 6    | 6    | 2    | 5     | 6    |
| Degradation %    | 1,96 | 9,16 | 3,98 | 10,85 | 3,01 |

| SIZE |     | ARTICLE NUMBER | EAN           |
|------|-----|----------------|---------------|
| 8    | M   | 7350-8         | 7392626013025 |
| 9    | L   | 7350-9         | 7392626059528 |
| 10   | XL  | 7350-10        | 7392626013032 |
| 11   | XXL | 7350-11        | 7392626035560 |

**ejendals**

Limavägen 28, SE-793 32 Leksand, Sweden  
Phone +46 (0) 247 360 00 | [info@ejendals.com](mailto:info@ejendals.com) | [order@ejendals.com](mailto:order@ejendals.com)