



A soft, comfortable, and heat resistant (up to 250° C/482° F) natural latex glove with perfect grip.

 TEGERA® CHEMFORCE 8160



[Learn more](#)

PROTECTS AGAINST WET AND CONTACT HEAT

A soft, comfortable, and heat resistant (up to 250° C/482° F) 0,5 mm/19,6 mil natural latex glove with perfect grip thanks to a foam pattern. Suitable for work in areas where there is a risk of contact heat injuries. Flexible chemical protection glove for allround work.

CHARACTERISTICS

- High level of protection
- Flexible
- Good grip
- Comfortable

FUNCTIONS

- Withstands contact heat up to 250°C
- Waterproof

PREVENTS RISK OF

Heat injuries, Contact with dirt, Contact with moisture, Contact with damp

PRIMARY ENVIRONMENTS OF USE

Slippery environments, Warm environments, Wet environments, Moist environments, Dirty environments

PRIMARY AREAS OF USE

Agricultural work, Building and construction, Cleaning, Concrete work, Decontamination, Hot work, Marine work, Paint spraying work, Painting, Paper industry work, Petro-chemical work, Sanitation, Wood industry work

PRIMARY INDUSTRIES OF USE

Agriculture, forestry and fishing, Pulp and paper, Building and construction

TYPE OF WORK

Medium weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE All-round work gloves, Chemical protection gloves, Heat protection gloves

CATEGORY Cat. III

COLLECTION Chemforce

THICKNESS 0,5* mm (*chem-layer)

LINING MATERIAL Interlock

LENGTH 300 mm

GRIP DESIGN Foam grip pattern

COLOUR Blue

PAIRS PER: BUNDLE/CARTON 12/120

DISPLAY TYPE Bulk pack

DIPPING Double-dipped

DIPPING MATERIAL Latex

INNER MATERIAL SPECIFICATION Cotton

OUTER MATERIAL SPECIFICATION Natural latex

COMPLIANCE

CEN 0598

TP TC 019:2011

UK CA Cat. III

EN ISO 21420:2020

EAC

EN 388:2016+A1:2018 3131X

EN 407:2020 (No flame protection) X2XXXX

EN ISO 374-5:2016

EN ISO 374-1:2016+A1:2018 Type B AKLPT



FEATURES



Waterproof



Chemical protection

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	A	K	L	P	T
Permeation level	2	2	3	5	6
Degradation %	-2,8	-7,7	55,7	-4,6	-21,9

SIZE		ARTICLE NUMBER	EAN
6	XS	8160-6	7392626008038
7	S	8160-7	7392626007543
8	M	8160-8	7392626007550
9	L	8160-9	7392626007567
10	XL	8160-10	7392626007574
11	XXL	8160-11	7392626007581

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com