Product group:	**Heating elements**
Type:	**Wraparound heater**
Status:	04-2025
Order no.:	see technical data
http://www.weldotherm.com	

Just check your set-up times!

If you frequently preheat and postheat pipes of the same diameter, you save time and money using our wraparounds.

Application limit: 950°C material temperature.

Application range: Preheating and Post heat treatment of circumferential joints.

The connection values are 30/60V AC, 45A, 1.35/ 2.7kW

All annealing mats come with a "DINSE" plug-in system as standard. "CAMLOCK" plug-in system on request.

Technical data

Order no.	Item	Voltage (V)	Outer Ø (mm)	Heater width (mm)	Power (kW)
201300	Wraparound heater 2"	30	60.3	126	1.35
201301	Wraparound heater 3"	60	88.9	168	2.7
201302	Wraparound heater 4"	60	114.3	147	2.7
201303	Wraparound heater 5"	60	141.3	126	2.7
201304	Wraparound heater 6"	60	168.3	189	5.4
201306	Wraparound heater 8"	60	219.1	147	5.4
201308	Wraparound heater 10"	60	273,0	189	8.1
201310	Wraparound heater 12"	60	323.8	189	8.1
201312	Wraparound heater 14"	60	355.6	189	10.8
201314	Wraparound heater 16"	60	406.4	168	10.8
201316	Wraparound heater 18"	60	457.2	189	13.5
201318	Wraparound heater 20"	60	508.0	168	13.5
201320	Wraparound heater 22"	60	558.8	189	16.2
201322	Wraparound heater 24"	60	609.6	189	18.9
201325	Wraparound heater 36"	60	914.4	168	24.3
201328	Wraparound heater 48"	60	1220,0	168	32,4