SIEMENS

Data sheet 6EP1322-2BA00



SITOP PSU100S/1AC/12VDC/7A

SITOP PSU100S 12 V/7 A stabilized power supply input: 120/230 V AC output: 12 V DC/7 A

General information	
Technical Product Detail Page	https://i.siemens.com/1P6EP1322-2BA00
product brand name	SITOP
product type designation	PSU100S
product designation	Power supply SITOP smart
type of current supply	12 V/7 A
input	
type of the power supply network	1-phase AC
phase number	1
voltage curve at input	AC
supply voltage at AC	Automatic range selection
supply voltage	120 V/230 V
input voltage 1 at AC	85 ... 132 V
input voltage 2 at AC	170 ... 264 V
supply voltage	
● at 50 Hz	230 V
● at 60 Hz	120 V
line frequency	50/60 Hz
line frequency	47 ... 63 Hz
wide range input	No
overvoltage overload capability	2.3 × Vin rated, 1.3 ms
buffering time for rated value of the output current in the event of power failure minimum	20 ms
operating condition of the mains buffering	at Vin = 93/187 V
input current	
● at rated input voltage 120 V	1.73 A
● at rated input voltage 230 V	0.99 A
current limitation of inrush current at 25 °C maximum	45 A
fuse protection type	T 3,15 A/250 V (not accessible)
fuse protection type in the feeder	Recommended miniature circuit breaker: from 6 A characteristic C
output	
voltage curve at output	Controlled, isolated DC voltage
product function output voltage controlled	Yes
product function output voltage stabilized	Yes
output voltage at DC rated value	12 V
output voltage	
● at output 1 at DC rated value	12 V
output voltage	
● at output 1 at DC	12 V

Subject to change without notice
© Copyright Siemens

output voltage adjustable	Yes; via potentiometer
adjustable output voltage	11.5 ... 15.5 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
● on slow fluctuation of input voltage	0.1 %
● on slow fluctuation of ohm loading	1 %
residual ripple	
● maximum	150 mV
● typical	20 mV
voltage peak	
● maximum	240 mV
● typical	100 mV
display version for normal operation	Green LED for 12 V OK
type of signal at output	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for 12 V OK
behavior of the output voltage when switching on	Overshoot of Vout < 3 %
response delay maximum	0.3 s
voltage increase time of the output voltage	
● typical	10 ms
output current	
● rated value	7 A
● rated range	0 ... 7 A; +50 ... +70 °C: Derating 0.75%/K
supplied active power typical	84 W
short-term overload current	
● on short-circuiting during the start-up typical	25 A
● at short-circuit during operation typical	25 A
duration of overloading capability for excess current	
● on short-circuiting during the start-up	800 ms
● at short-circuit during operation	800 ms
bridging of equipment	Yes
number of parallel-switched equipment resources for increasing the power	2
efficiency	
efficiency in percent	84 %
power loss [W]	
● at rated output voltage for rated value of the output current typical	15 W
closed-loop control	
relative control precision of the output voltage at load step of resistive load 10/90/10 % typical	5 %
setting time	
● load step 10 to 90% typical	1 ms
● load step 90 to 10% typical	1 ms
protection and monitoring	
design of the overvoltage protection	< 20 V
property of the output short-circuit proof	Yes
design of short-circuit protection	Constant current characteristic
response value current limitation	7 ... 8.8 A
overcurrent overload capability	
● in normal operation	overload capability 150 % Iout rated up to 5 s/min
enduring short circuit current RMS value	
● typical	8.8 A
safety	
electrical separation between input and output	Yes
electrical separation	Output voltage: SELV, ES1 (IEC 62368-1), DVC As (IEC 61204-7)
operating resource protection class	Class I
leakage current	
● maximum	3.5 mA
● typical	0.4 mA
protection class IP	IP20

© Copyright Siemens

EMC	
standard	
● for emitted interference	EN 55022 Class B
● for mains harmonics limitation	EN 61000-3-2
● for interference immunity	EN 61000-6-2
standards, specifications, approvals	
certificate of suitability	
● CE marking	Yes
● UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
● UKCA marking	Yes
● EAC approval	Yes
● NEC Class 2	No
type of certification	
● CB-certificate	Yes
MTBF at 40 °C	1 998 441 h
standards, specifications, approvals hazardous environments	
certificate of suitability	
● IECEx	No
● ATEX	No
● ULhazloc approval	No
● FM registration	No
standards, specifications, approvals marine classification	
shipbuilding approval	Yes
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	No
● French marine classification society (BV)	No
● Det Norske Veritas (DNV)	Yes
● Lloyds Register of Shipping (LRS)	No
standards, specifications, approvals Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	420.1 kg
● during manufacturing	12.9 kg
● during operation	406.7 kg
● after end of life	0.37 kg
ambient conditions	
ambient temperature	
● during operation	-25 ... +70 °C; with natural convection
● during transport	-40 ... +85 °C
● during storage	-40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
connection method	
type of electrical connection	screw terminal
● at input	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm² single-core/finely stranded
● at output	+, -: 2 screw terminals each for 0.5 ... 2.5 mm²
● for auxiliary contacts	Alarm signals: 2 screw terminals for 0.5 ... 2.5 mm²
● for signaling contact	2 screw terminals for 0.5 ... 2.5 mm²
mechanical data	
width × height × depth of the enclosure	50 × 125 × 120 mm
installation width × mounting height	50 mm × 225 mm
required spacing	
● top	50 mm
● bottom	50 mm
● left	0 mm
● right	0 mm
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
● DIN-rail mounting	Yes
● S7 rail mounting	No

Subject to change without notice
© Copyright Siemens

● wall mounting	No
housing can be lined up	Yes
net weight	0.5 kg

further information internet links

internet link	
● to website: Industry Mall	https://mall.industry.siemens.com
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to web page: power supplies	https://siemens.com/sitop
● to website: CAx-Download-Manager	https://siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

additional information

other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Classifications

	Version	Classification
eClass	16	27-04-07-01
eClass	14	27-04-07-01
eClass	12	27-04-07-01
eClass	9.1	27-04-07-01
eClass	9	27-04-07-01
eClass	8	27-04-90-02
eClass	7.1	27-04-90-02
eClass	6	27-04-90-02
ETIM	10	EC002540
ETIM	9	EC002540
ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

Approvals Certificates

Environmental Product Declaration

● global warming potential [CO2 eq] / during manufacturing	12.9 kg
● global warming potential [CO2 eq] / during operation	406.7 kg
● global warming potential [CO2 eq] / after end of life	0.37 kg
● global warming potential [CO2 eq] / total	420.1 kg

Environment	General Product Approval				
EPD	CB	Manufacturer Declaration	Declaration of Conformity	UKCA	CE EG-Konf.

Subject to change without notice
© Copyright Siemens

General Product Approval			Maritime application
China RoHS		Miscellaneous	

last modified: 8/29/2026

Subject to change without notice
© Copyright Siemens